



SPRING DIGITAL

8000 SERIES

VINYL FOR CUTTING PLOTTERS



Cutting plotter
FC8600 Series
FC8600 series Graphitec's Flagship Cutting Plotter.
Providing the high performance
and functions and greater ease of use.

 Long length cutting for 50 feet



SPRING DIGITAL

8000 SERIES

PROFESSIONAL GLOSS GRAPHIC VINYL

Film: 80 micron gloss monomeric calendered vinyl

Adhesive: clear permanent acrylic based adhesive

Backing: one side PE coated paper
140g/m²



SPRING DIGITAL

8000 SERIES

PROFESSIONAL MATT GRAPHIC VINYL

Film: 80 micron matt monomeric calendered vinyl
Adhesive: clear permanent acrylic based adhesive
Backing: one side PE coated paper
140g/m²



SPRING DIGITAL

8000 SERIES

PROFESSIONAL GLOSS / MATT GRAPHIC VINYL

TECHNICAL SPECIFICATIONS

Outdoor Durability

1 year

Regular Roll Size

Width 610mm / 1220mm x Height 50 mtrs

METHOD OF INSTALLATION - YOUR CHEAT SHEET!

1. Use transfer tape to easily install your vinyl letters on to the desired surface. The transfer tape (sticky side) is to be directly placed on top of your vinyl letters.
2. After measuring and marking where you want your lettering to be applied, affix the graphic with the help of the transfer tape to the wall.
3. Now slowly start removing the backing from top to bottom with the transfer tape remaining over the cut vinyl.
4. Working from top to bottom use a squeegee or flat edge to apply the letters to the wall while continuing to slowly pull the backing off. Once fully applied, slowly and carefully peel away the transfer tape.
4. Your vinyl lettering is now applied to the wall.

APPLICATION KNOWLEDGE

- Graphic vinyl is to be applied on a smooth, non-porous surface. Thus metal, glass, plastic, painted drywall, tile, painted wood, and more are great places to put your lettering.
- Graphic vinyl works on the interior or exterior of all types of vehicles. This includes both cars and trucks as well as boats.
- The majority of lettering can simply be peeled away like any other sticker. Use a sharp edge may be needed to remove lettering that has been in place for extended periods of time.

SPRING DIGITAL

8000 SERIES

PROFESSIONAL GLOSS / MATT GRAPHIC VINYL

APPLICATION KNOWLEDGE (CONT.)

- Graphic vinyl should not be applied to any surface that has been very recently painted. Painted surfaces should be allowed 2-3 weeks to dry and cure properly before applying the lettering. Doing so sooner risks damage to the paint.
- Your vinyl letters will work best on semi-gloss and glossy paints. Generally speaking latex and oil based paints will work. This covers the majority of homes and businesses. Alternatively, faux, flat, satin, magnetic suede and sand paints will not work well with the vinyl's adhesive.
- Graphic vinyl can be used for storefront advertising, sales and promotions, decor, motivational quotes, room numbering, vehicle ads, as well as no soliciting, security warnings, and much more.
- Graphic vinyl is opaque, but thin enough that some light will pass through when installed on windows. The darker the color, the more opaque it tends to be.
- Graphic vinyl can be made visible from outside with certain adjustments while creating the design. This is called "Reverse Cut" and should be selected as an option on the cutting plotter.
- Graphic vinyl will work just fine in humid locations or rooms and climates. The only exception to this is a surface(s) that is wet when applied as the adhesive won't properly adhere when initially installed. Extremely humid locations may reduce the lifespan of the decal but the lettering should still last years with proper installation and care.
- Cut-up graphic vinyl can be stored for a short period (no greater than 1-2 months) but should be installed as soon as possible to ensure that the adhesive works correctly when applied.
- Graphic vinyl will work on tinted windows. The caveat is that the sign and lettering needs to be designed with this in mind. A light color or white should be used to provide the needed contrast to ensure maximum visibility of the sign. Dark colors on a dark or tinted window will not be very visible, if at all.

SPRING DIGITAL

8000 SERIES

PROFESSIONAL GLOSS / MATT GRAPHIC VINYL

APPLICATION KNOWLEDGE (CONT.)

Also, all installation on tinted glass should always be done on the side of the window where you want the lettering visible to the customer. Don't attempt to install in a way that you look through the tinted glass to see the lettering.

- Graphic vinyl can be used for both indoor and outdoor application. Climate, installation and care and maintenance will impact the lifespan of the lettering but they should last 2-3 years.



P.O.Box.55469 Dubai U.A.E
Showroom No. 2 Al Mansour Building
Damascus Street Al Qusais
Tel +9714 280 64 10 Fax +9714 280 64 70
Email adsadver@emirates.net.ae
Web www.ads-adv.com

